

# [Xray Server] Wrong Execution Result is taken over to Requirement Status

## Problem

Although the last run of a Test was passed, the Requirement Status of the linked issue is not taking the latest execution result:

Key	Fix Version/s	Revision	Executed By	Started	Finished	Defects	Summary	Priority	Created	Begin Date	Status	
680				06/Aug/20 8:52 AM	1 minute ago				22/Jun/20	14/Sep/20 12:48 PM	PASS	
669				05/Aug/20 8:44 AM	05/Aug/20 8:44 AM				08/Jun/20	31/Jul/20 12:47 PM	FAIL	
569				18/Jun/20 5:51 PM	10/Jul/20 4:13 PM				26/May/20	13/May/20 7:33 AM	FAIL	

Showing 1 to 3 of 3 entries

FirstPrevious1NextLast

### Test Coverage

Create TestCreate Sub-Test Execution+ Link

TEST COVERAGE FOR THE FOLLOWING ANALYSIS SCOPE

Scope: Version; Version: None - latest execution; Environment: All Environments

NOK

Filter(s)

Show 10 entriesColumns

P	Status	Resolution	Key	Summary	Test Runs	Test Status
	TEST READY	Unresolved			10	FAIL

## Possible Causes

Xray has a Tool called **Final statuses have precedence over non-final statuses**; when it is Unchecked, the Latest Test Run Status Calculation will always consider the **Latest Created** Test Run.

Now, a Test Run is only created when a Test is associated with a Test Execution.

In the provided example, the Test Execution with the key **680[PASS]** was created after **669[FAIL]**, but the Test Execution **680[PASS]** was associated with the Test before the **669[FAIL]**, so the latest Test Run is from **669[FAIL]**.

The mentioned option is in Jira Administration Manage apps Xray -> Manage Test Statuses:

ATLASSIAN MARKETPLACE

Find new apps

Manage apps

XPORTER

Global Settings

Project Settings

Integrations

Templates

Scheduled Reports

Permission Schemes

File Servers

Post Function Authentication

Xporter Audit Log

Process Manager

Export and Import

License Management

Documentation

XRAY

Miscellaneous

Custom Fields

Issue Type Mapping

Recent Changes

Test Statuses

Manage custom Test Run statuses for Xray

Name	Description	Final	Color	Requirement Status	Operations
PASS	The test run has passed	<input checked="" type="checkbox"/>	<div></div>	OK	
TODO	The test run has not started	<input type="checkbox"/>	<div></div>	NOTRUN	
EXECUTING	The test run is currently being executed	<input type="checkbox"/>	<div></div>	NOTRUN	
FAIL	The test run has failed	<input checked="" type="checkbox"/>	<div></div>	NOK	
ABORTED	The test run was aborted	<input checked="" type="checkbox"/>	<div></div>	NOTRUN	
BLOCKED		<input type="checkbox"/>	<div></div>	NOTRUN	<a href="#">Edit</a> <a href="#">Delete</a>
PENDING		<input type="checkbox"/>	<div></div>	UNKNOWN	<a href="#">Edit</a> <a href="#">Delete</a>
FAIL_DISCARDABLE	FAIL_DISCARDABLE	<input type="checkbox"/>	<div></div>	UNKNOWN	<a href="#">Edit</a> <a href="#">Delete</a>
FAILING_BUT_OK	this is failing but we can go to production	<input type="checkbox"/>	<div></div>	OK	<a href="#">Edit</a> <a href="#">Delete</a>

Create

Preferences

☐ Final statuses have precedence over non-final statuses

When this option is enabled, the latest Test Issue Status is calculated based on the latest Test Run with a final status. Otherwise, this calculation will always consider the latest created Test Run even if the status is non-final.

Save

# Link for related documentation

*Final statuses have precedence over non-final statuses*