

Sub-Test Execution

A Sub-Test Execution has exactly the same functionalities as the [Test Execution](#) issue type. The difference between them is that the Sub-Test Execution is a **sub-task** and can be created within the context of a **requirement**.

Creating a Test Execution as a sub-task of the requirement issue provides you the ability to track executions in the Agile board.

Create Sub-Test Executions

To create a new Sub-Test Execution, click the **Create new Test Execution** button in the **Test Coverage** section in the **Requirement Issue View**:

XPack / XP-6

As a user, I can login into the app using Facebook authentication

EditCommentAssignMore

Start ProgressResolve IssueClose IssueAdmin

Details

Type: Story
Priority: Medium
Labels: None
Requirement Status: NOT RUN

Status: OPEN (View Workflow)
Resolution: Unresolved

People

Assignee: admin
Reporter: admin
Votes: 0
Watchers: Stop watching this issue

Dates

Created: 41 minutes ago
Updated: 12 minutes ago

HipChat discussions

Do you want to discuss this issue? Connect to HipChat.
ConnectDismiss

Description

Click to add description

Test Coverage

Version: No Version
Create new TestCreate new Test ExecutionNOT RUN
OPEN XP-15 qwe

Attachments

Drop files to attach, or browse.

Issue Links

tested by XP-15 qwe

Sub-Tasks

1. Execution for Facebook authentication (iOS Systems) REOPENED admin
2. Execution for Facebook authentication (Android Systems) OPEN admin

Remember to Associate Tests and Test Sets with the Sub-Test Execution.