

Test Executions - REST

You can manage (i.e., create, update, delete) Test Executions directly through [Jira's native REST API](#).

The Xray REST API provides the following endpoints.

Test Execution Tests

- To view the Tests associated with a Test Execution, you need to specify the key of the Test Execution you want to view.
- To associate or remove a Test from a Test Execution, you need to send a JSON with a list of the keys. When associating, these keys can be Test keys or Test Set keys; when removing, they have to be Test keys.
- To remove a Test from a Test Execution, you need to specify the key of the Test you wish to remove.

Return a json with a list of the test associated with the test execution. Note that this endpoint may be paginated.

Request

PATH PARAMETERS

parameter	type	description
testExecKey	String	- key of the test execution.

QUERY PARAMETERS

parameter	type	description
detailed	boolean	- if true will display detailed information about the testrun
limit	integer	- limits the number of results per page. Should be greater or equal to 0 and lower or equal to the maximum set in the Global Configuration.
page	integer	- number of the page to be returned. Should be greater or equal to 1.



Example Request

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testexec/TEST-123/test

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testexec/TEST-123/test?detailed=true

Responses

200 OK : **text/plain** : Successful. Return a json.

Example Output

```
[
  {
    "id":204,
    "key":"CALC-10",
    "rank":1,
    "status":"FAIL"
  },
  {
    "id":205,
    "key":"CALC-44",
    "rank":2,
    "status":"FAIL"
  },
  {
    "id":326,
    "key":"CALC-66",
    "rank":3,
    "status":"TODO"
  },
  {
    "id":380,
    "key":"CALC-42",
    "rank":4,
    "status":"TODO"
  }
]
```

Example Output

```
[
  {
    "id":204,
    "status":"FAIL"
    "assignee":"admin",
    "executedBy":"admin",
    "startedOn":"Friday 10:13 AM",
    "finishedOn":"Friday 10:13 AM",
    "defects":[
      {
        "id":10607,
        "key":"PER-71",
        "summary":"1234",
        "status":"Open"
      }
    ],
    "evidences":[
      {
        "id":25,
        "fileName":"stepsDATA.csv",
        "fileSize":"0,1 KB",
        "created":"Friday 10:16 AM",
        "author":"admin",
        "fileURL":"http://localhost:5980/testJira/plugins/servlet/raven/attachment/25/stepsDATA.csv"
      }
    ],
    "key":"PER-46",
    "rank":1
  },
  {
    "id":60,
    "status":"FAIL",
    "executedBy":"admin",
    "startedOn":"Friday 10:13 AM",
    "finishedOn":"Friday 10:13 AM",
    "defects":[
    ],
    "evidences":[
    ],
    "key":"PER-41",
    "rank":2
  },
  {
    "id":61,
    "status":"ABORTED",
    "executedBy":"blake",
    "startedOn":"Friday 10:13 AM",
    "finishedOn":"Friday 10:13 AM",
    "defects":[
    ],
    "evidences":[
    ],
    "key":"PER-33",
    "rank":3
  }
]
```

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray for JIRA license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred getting the tests.

Associate tests with the test execution. Return error messages, if there are any.

Request

PATH PARAMETERS

parameter	type	description
testExecKey	String	- key of the test execution.

Example

Example Input

```
{
  "add": [
    "CALC-33",
    "CALC-75"
  ],
  "remove": [
    "CALC-25",
    "CALC-45"
  ]
}
```



Example Request

```
curl -H "Content-Type: application/json" -X POST -u admin:admin --data @example.json http://yourserver/rest/raven/1.0/api/testexec/TEST-123/test
```

Responses

200 OK : **text/plain** : Successful. Return error messages, if there are any.

Example Output

```
["Issue with key CALC-99 not found or is not of type Test or Test Set."]
```

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray for JIRA license is not valid.

500 INTERNAL_SERVER_ERROR : **text/plain** : An internal error occurred associating the tests.

Removetestfrom the test execution.

Request

PATH PARAMETERS

parameter	type	description
testExecKey	<i>String</i>	- key of the test execution.
testKey	<i>String</i>	- key of the test.



Example Request

```
curl -H "Content-Type: application/json" -X DELETE -u admin:admin http://yourserver/rest/raven/1.0/api/testexec/TEST-123/test/TEST-321
```

Responses

200 OK : **text/plain** : Successful.

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray for JIRA license is not valid.

500 INTERNAL_SERVER_ERROR : **text/plain** : An internal error occurred removing the test.