

Export Cucumber Features

Cucumber .feature files can be exported from Xray and executed externally. They can be generated from the following Xray issues:

- Test
- Test Set
- Test Execution
- Test Plan

Or, from an Issue mapped as a Requirement issue type.

If the **language** defined to export the cucumber .feature files is not the default (i.e., En), then a language tag will be added.

Rules

Xray generates Cucumber .feature files according to the context issue and the following rules:

Test:

- A single Cucumber **feature** file is generated for each **requirement** associated with this Test.
- The feature contains the **feature header** description of the associated requirement, if present.
- The feature contains the **background** of the Test, if present in the Pre-Condition associated with it.
- The feature contains the **Scenario/Scenario Outline** defined in this Test.

Test Set, Test Execution, Test Plan or Requirement issue:

- A single Cucumber **feature** file is generated for each different tuple (**Requirement, Pre-Condition**).
- A Test Execution does not contain repeated tests.
- If a Test is not associated with a requirement, then it will be exported as an independent feature file.
- If a Test is associated with more than one requirement, then a feature file will be generated for each requirement. The generated .feature files will contain repeated test scenarios.
- The feature contains the **feature header** description of the associated requirement, if present.
- The feature contains the common **background** of the Tests, if present in the Pre-Condition.
- The feature contains the **Scenario/Scenario Outline** for all the tests.

Feature File Format

```
[ #language: { language } ]
[ @{ Test Execution issue Key } ]
[ @{ Requirement issue Key } ]
Feature: [{ Requirement Issue Summary }]
        [{ Requirement Issue Description }]

    [Background:
      { Pre-Conditions }]

    [# { Test Issue Description }]
    @{ Test Issue Key }
    [{@{ SubRequirement Issue Key 1 } ... @{ SubRequirement Issue Key N }]
    [{@{ Test Set Issue Key 1 } ... @{ Test Set Issue Key N }]
    [{@{ Test Issue Label 1 } ... @{ Test Issue Label N}]
    Scenario [Outline]: { Test Issue Summary }
      {Test Issue Steps}
    ...
```

Feature File Naming Convention

```
<sequential_id_one_based>[_<issue_requirement_key>][_<issue_precondition_key>]
```

Example

Exporting a Test Execution with the following Tests:

Key	Requirement	Pre-Condition
T1	R1	C1

T2	R1	-
T3	-	C2
T4	R2	C1
T5	R2	C3
T6	-	-
T7	R2, R3	C1
T8	R2, R3	-
T9	-	C2
T10	R1	C1

generates the following **9** feature files:

File	Requirements	Pre-Condition	Tests	Filename
1	R1	C1	T1, T10	1_R1_C1.feature
2	R1	-	T2	2_R1.feature
3	R2	C1	T4, T7	3_R2_C1.feature
4	R2	C3	T5	4_R2_C3.feature
5	R2	-	T8	5_R2.feature
6	R3	-	T8	6_R3.feature
7	R3	C1	T7	7_R3_C1.feature
8	-	C2	T3, T9	8_C2.feature
9	-	-	T6	9.feature