

Testing using Robot framework and xUnit reports

Overview

In this tutorial, we will execute some tests using the [Robot Framework](#).

Please note

This tutorial explores the integration using the JUnit XML report that the Robot Framework is capable of generate.

Since the Robot Framework native XML format is supported by Xray, it is the preferable way of importing tests/results from Robot test cases. Whenever integrating through Robot's specific XML format, you have access to more features than the ones that are available if you use JUnit's XML format, since the latter is a generic format.

Requirements

- robot framework
- Java (if using the Java variant of the "robot framework")

Description

This and more examples may be found in Robot framework's [robotdemo repository](#).

calculator.py

```
class Calculator(object):
    BUTTONS = '1234567890+-* /C='
    def __init__(self):
        self._expression = ''
    def push(self, button):
        if button not in self.BUTTONS:
            raise CalculationError("Invalid button '%s'." % button)
        if button == '=':
            self._expression = self._calculate(self._expression)
        elif button == 'C':
            self._expression = ''
        elif button == '/':
            self._expression += '//'    # Integer division also in Python 3
        else:
            self._expression += button
        return self._expression
    def _calculate(self, expression):
        try:
            return str(eval(expression))
        except SyntaxError:
            raise CalculationError('Invalid expression.')
        except ZeroDivisionError:
            raise CalculationError('Division by zero.')

class CalculationError(Exception):
    pass
```

The Robot test:

keyword_driven.robot

```
*** Settings ***
Documentation      Example test cases using the keyword-driven testing approach.
...
...               All tests contain a workflow constructed from keywords in
...               ``CalculatorLibrary.py``. Creating new tests or editing
...               existing is easy even for people without programming skills.
...
...               The _keyword-driven_ approach works well for normal test
...               automation, but the _gherkin_ style might be even better
...               if also business people need to understand tests. If the
...               same workflow needs to repeated multiple times, it is best
...               to use to the _data-driven_ approach.
Library            CalculatorLibrary.py
*** Test Cases ***
Push button
    Push button    1
    Result should be    1
Push multiple buttons
    Push button    1
    Push button    2
    Result should be    12
Simple calculation
    Push button    1
    Push button    +
    Push button    2
    Push button    =
    Result should be    3
Longer calculation
    Push buttons    5 + 4 - 3 * 2 / 1 =
    Result should be    3
Clear
    Push button    1
    Push button    C
    Result should be    ${EMPTY}    # ${EMPTY} is a built-in variable
```

After running the tests and generating the JUnit XML report (e.g., [robot.xml](#)), it can be imported to Xray (by using either the REST API or the **Import Execution Results** action within the Test Execution).

If you're using Python,

```
robot -x robot.xml keyword_driven.robot
```

If you're using Java,

```
java -jar robotframework-3.0.jar -x robot.xml keyword_driven.robot
```

JUnit's Test Case is mapped to a Generic Test in Jira, and the **Generic Test Definition** field contains the friendly name of the Robot script concatenated with the alias of the test case.

Tests

Create Test

+ Add

Overall Execution Status

TOTAL TESTS: 5

5 PASSED

Filters

10

Columns

Key	Summary	Test Type	Assignee	Status	Actions
<input type="checkbox"/> CALC-321	Push multiple buttons	Generic	Unassigned	<div></div> PASSED	<div></div> ...
<input type="checkbox"/> CALC-317	Simple calculation	Generic	Unassigned	<div></div> PASSED	<div></div> ...
<input type="checkbox"/> CALC-318	Clear	Generic	Unassigned	<div></div> PASSED	<div></div> ...
<input type="checkbox"/> CALC-319	Push button	Generic	Unassigned	<div></div> PASSED	<div></div> ...
<input type="checkbox"/> CALC-320	Longer calculation	Generic	Unassigned	<div></div> PASSED	<div></div> ...

Prev 1 Next

Total 5 issues

The Execution Details of the Generic Test contains information about the Test Suite, which in this case corresponds to the friendly name of the robot script (i.e., "Keyword Driven").

Test Details

Test Type:

Generic

Definition:

Keyword Driven.Push multiple buttons

Results

Context	Error Message	Duration	Status
TestSuite Keyword Driven	-	-	PASSED

References

- <http://robotframework.org/>
- <https://bitbucket.org/robotframework/robotdemo/src>
- <https://github.com/robotframework/robotframework/blob/master/INSTALL.rst>