

Coverage Analysis

- [Analysis Scopes](#)
 - [Latest](#)
 - [Version](#)
 - [Test Plan](#)
 - [Test Environment](#)
 - [Final Statuses Precedence](#)
- [Analyzing Xray entities](#)
 - [Coverable issues](#)
 - [Issue screen](#)
 - [Reports](#)
 - [Test Coverage](#)
 - [Tests](#)
 - [Issue screen](#)
 - [Reports](#)
 - [Tests List](#)
 - [Test Sets](#)
 - [Reports](#)
 - [Tests Sets List](#)
- [Troubleshooting](#)



Learn more

Please read [Understanding the calculation of coverage status and the status of Tests](#) for an in-depth explanation of the calculation of these statuses.

Analysis Scopes

Tests and coverable issues can be analyzed from different perspectives/scopes.

The same Test or Story can be analyzed, for example, on version 1.0 and also on version 2.0. This will take into account the respective executions made for those versions.

Therefore, a Story may be OK on version 1.0, but may be NOK on version 2.0 due to regression.

Tests and coverable issues can be analyzed from these scopes (or dimensions):

- **Latest**
- **Version**
- **Test Plan**

They can also be analyzed based with some additional criteria that will affect the calculated values, such as:

- **Test Environment**
- **Final statuses precedence over non-final ones**

Latest

If you don't care about versions, or you're not using versions at all and just want to see the calculated statuses based on the latest runs, analysis by "Latest" can be used for that purpose.

This is useful to have a quick view of the latest results or calculated status for the Test or coverable issue.

Note that when analyzing by latest results, it also considers the latest results made in the different environments (i.e., when "All Environments" is selected as Test Environment).

Version

The "Version" scope allows users to analyze Tests and coverable issues from a version perspective. It helps address such questions as

- "How is the requirement on version X?"
- "How are these Tests performing on version Y?"

When analyzing by version, only the Test Executions made for the given version are considered (i.e., the Test Execution's Fix Version field).

As an example, a user story aimed for version 3.0 may be analyzed from the point of view of the executions made for version 3.0 or for the ones made afterwards on version 4.0.

Test Plan

This gives you the ability to evaluate the Test status or coverage status based on some planned testing (i.e., on the Tests and related executions made in the scope of the selected Test Plan).

When analyzing by Test Plan, only the Test Executions linked to that Test Plan are considered.

This allows you to evaluate if a given coverable issue is covered by the Tests of some Test Plan or not. If so, then you can see how is it going based on the executions performed from the related planned Test Executions.

Test Environment

Analysis by Test Environment gives the ability to analyze the Test status or the coverage status of an issue for some Test Environment.

It addresses such questions as "How is this requirement doing on environment X?"

When analyzing by Test Environment, only Test Executions made for the given Test Environment are considered.

Final Statuses Precedence

Final statuses precedence is used to perform the analysis based on "finished work" (non-intermediate Test Runs).

The flag "Final statuses have precedence over non-final statuses" gives the additional ability to consider just those Test Runs whose status is configured as being a final status.

This helps address questions such as:

- "What is the current status of this requirement (or test)?" (if final statuses precedence is unchecked)
- "What is the status of this requirement (or test), considering just the finished work?" (if final statuses precedence is checked)

Analyzing Xray entities

Xray entities can be analyzed in the issue view screen as well as in specific reports containing those entities.

Coverable issues

The status of coverable issues can be evaluated directly in the issue view screen as well as on some reports, including the Tests Coverage report.

Issue screen

Within the issue screen, the coverage status can be evaluated for the specified scope within the Test Coverage section. The calculated coverage status is shown on the right side.

As a visitor, I can Checkout items in my basket

Attach

Create subtask

Link issue

▼

Test Coverage

...

Description

As a visitor of the book store website
I want to be able to do a purchase
So that I can get the product that I want

Environment

None

Linked issues

+

is tested by

STORE-24 Test a visitor can Checkout items in his basket

↑

TO DO ▼

STORE-25 Test Checkout with incorrect delivery details

↑

TO DO ▼

Test Coverage

...

Create Test

Create Sub Test Execution

Calculate the Test Coverage for the following scopes.

Latest

Version

Test Plan

Test Environment

All Environments ▼

☒ Final statuses have precedence over non-final.

OK

Status	Key	Summary	Test Status
↑ .. TO DO	STORE-24	Test a visitor can Checkout items in his basket	<div>PASSED</div>
↑ .. TO DO	STORE-25	Test Checkout with incorrect delivery details	<div>PASSED</div>

Prev 1 Next

Reports

Test Coverage

Coverable issues can be analyzed for a given scope using the Test Coverage report. More info about this report in [Test Coverage Report](#). The chosen scope will be store in the user preferences, and will affect all issues in the same project.

Test Coverage Report ?

Share

Analysis & Scope

Scope: Version Version: 3.0 Final Status

Group By


Priority

View

Hierarchical

Filters

Project: Book Store



Tests

The status of Tests can be evaluated directly in the Test issue view screen as well as on some reports, including the Tests List report and, indirectly, the Test Sets List report.

Tests can also be evaluated in the coverable issue screen, within the "Test Coverage" section.

Issue screen

Within the Test issue screen, the Test status can be evaluated for the specified scope. The calculated status is cached for performance reasons. Since data between Jira and Xray may not be in sync, it's possible to enforce a recalculation to display an up-to-date value. The chosen scope will be store in the user preferences, and will affect all issues in the same project.

Projects / Book Store / STORE-24

Test a visitor can Checkout items in his basket

Attach Create subtask Link issue Test Details

Description

Add a description...

Environment

None

Linked issues

tests

STORE-6 As a visitor, I can Checkout items in my basket

TO DO

Test Status

PASSED

Calculate the latest Test Status for the following scopes.

Latest

Version

Test Plan

Test Environment

All Environments

Final statuses have precedence over non-final.

Recalculate

Reports

Tests List

The Tests can be analyzed for a given scope using the Tests List report.

Tests List ?

[Share](#) [Export](#)

Analysis & Scope

Scope: Version Version: 3.0 Final Status

Filters

Project: Book Store

10

Columns

Key	Summary	Test Type	Status	Status
STORE-19	Test visitors can Login to Book Store Website	Cucumber	TO DO	TO DO
STORE-20	Test logged in visitors can Logout from their account	Cucumber	TO DO	TO DO
STORE-21	Test a logged in visitor can edit the account details	Cucumber	TO DO	TO DO
STORE-22	Test a logged in visitor can edit the default address	Cucumber	TO DO	TO DO
STORE-23	Test a visitor can change his locale	Cucumber	TO DO	TO DO
STORE-24	Test a visitor can Checkout items in his basket	Cucumber	TO DO	TO DO
STORE-25	Test Checkout with incorrect delivery details	Cucumber	TO DO	TO DO
STORE-26	Test visitors can signup to the book store Newsletter	Cucumber	TO DO	TO DO
STORE-27	Test visitors can unsubscribe from the book store Newsletter	Manual	TO DO	TO DO
STORE-28	Test visitors can navigate to the book details page	Cucumber	TO DO	TO DO

Prev

12345Next

Total 42 issues

Test Sets

The status of Test Sets (i.e., of the Tests contained within a Test Set) can be analyzed using the Test Sets List report.

Reports

Tests Sets List

The Test Sets, and implicitly the Tests within them, can be analyzed for a given scope using the Test Sets List report.

Test Sets List ?

[Share](#) [Export](#)

Analysis & Scope

Scope: Version Version: 3.0 Final Status

Filters

Project: Book Store

10

Columns

Key	Summary	Fix versions	Test Count	Status
STORE-42	Subscription		2	
STORE-41	Account Tests		5	

TO DO

5

Total:

5

TO DO: 5 (100%)

Prev1Next

Total 2 issues

Troubleshooting

"I have an Xray Project to Test my Requirements project. I've created a Test and I have already executed the Test, but I always get Requirements status Covered but Not Run."



You might be using environments on Test Executions that are affecting the aggregated status for the Tests. If you have a couple of Test Executions, one with a specific environment (e.g., Android) and another without any environment, then Xray will also consider the empty environment when calculating the aggregated status (this is, of course, if all Test Executions are within the same Version or Test Plan).



You probably have not configured your versions properly. Remember that coverage status of some issue for some version is calculated based on the Fix Version associated with the [Test Execution](#) issues.

[Back to top](#)

