Test Runs - REST

Test Runs

- Test Runs
  - Test Run
  - Status
  - Execution Defects
  - Execution Evidence
  - Comment
  - Examples
  - Test Steps

Test Run

- To view a Test Run, you need to specify the ID of the Test Run. Another way to view a Test Run is to specify the Test Exec and Test Issue to which the Test Run belongs.
- To update a Test Run, you need to send a JSON with the Test Run fields you want to update.

Return a json that represents the test run.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- id of the test run.

Example Request

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testrun/2

Responses

200 OK : **text/plain** : Successful. Return a json that represents the test run.

Example Output

```
{
   "id":371,
   "status":"TODO",
   "testKey":"CALC-12",
   "testExecKey":"CALC-13",
   "assignee":"admin",
   "executedBy":"admin",
   "startedOn":"2016-10-11T17:14:03+01:00",
   "finishedOn": "2016-10-24T14:58:35+01:00",
   "duration": 1115072328,
   "defects":[
      {
         "id":15017,
         "key":"test-114",
         "summary":"summary 1",
         "status":"Open"
      },
      {
         "id":15018,
         "key":"test-115",
         "summary":"summary 2",
         "status":"Open"
      }
   ],
   "evidences":[
```

```
      {
         "id":313,
         "fileName":"stuff.txt",
         "fileSize":"0,0 kB",
         "created":"2016-10-24T15:50:57+01:00",
         "author":"admin",
         "fileURL":"http://lenovo-pc:2990/jira/plugins/servlet/raven/attachment/313/stuff.txt"
      },
      {
         "id":314,
         "fileName":"stuff2.txt",
         "fileSize":"0,0 kB",
         "created":"2016-10-24T15:50:57+01:00",
         "author":"admin",
         "fileURL":"http://lenovo-pc:2990/jira/plugins/servlet/raven/attachment/314/stuff2.txt"
      }
   ],
   "comment":"new comment",
   "scenarioOutline":"Given I have entered <input_1> into the calculator\r\nAnd I have entered <input_2> into
the calculator\r\nWhen I press <button>\r\nThen the result should be <output> on the screen\r\n\r\n  Examples:
\r\n    | input_1 | input_2 | button | output |\r\n    | 20      | 30      | add    | 50     |\r\n    |
2       | 5       | add    | 7      |\r\n    | 0       | 40      | add    | 40     |",
   "examples":[
      {
         "id":1377,
         "rank":0,
         "values":[
            "input_1",
            "input_2",
            "button",
            "output"
         ],
         "status":"PASS",
         "statusDescription":"The test run has passed"
      },
      {
         "id":1378,
         "rank":1,
         "values":[
            "20",
            "30",
            "add",
            "50"
         ],
         "status":"PASS",
         "statusDescription":"The test run has passed"
      },
      {
         "id":1379,
         "rank":2,
         "values":[
            "2",
            "5",
            "add",
            "7"
         ],
         "status":"PASS",
         "statusDescription":"The test run has passed"
      },
      {
         "id":1380,
         "rank":3,
         "values":[
            "0",
            "40",
            "add",
            "40"
         ],
         "status":"PASS",
         "statusDescription":"The test run has passed"
      }
```

```
   ],
   "environments" : [
          "IOS",
          "Android"
          ]
}
```

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred getting the test run.

Return a json that represents the test run.

Request

QUERY PARAMETERS

parameter	type	description
testExecIssueKey	*String*	- key of the Test Execution.
testIssueKey	*String*	- key of the Test Issue.

Example Request

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testrun?testExecIssueKey=TEST-123&testIssueKey=TEST-321

Responses

200 OK : **text/plain** : Successful. Return a json that represents the test run.

Example Output

```
{
   "id":371,
   "status":"TODO",
   "testKey":"CALC-12",
   "testExecKey":"CALC-13",
   "assignee":"admin",
   "executedBy":"admin",
   "startedOn":"2016-10-24T15:50:57+01:00",
   "defects":[
      {
         "id":15017,
         "key":"test-114",
         "summary":"summary 1",
         "status":"Open"
      },
      {
         "id":15018,
         "key":"test-115",
         "summary":"summary 2",
         "status":"Open"
      }
   ],
   "evidences":[
      {
         "id":313,
         "fileName":"stuff.txt",
         "fileSize":"0,0 kB",
```

```
         "created":"2016-10-24T15:50:57+01:00",
         "author":"admin",
         "fileURL":"http://lenovo-pc:2990/jira/plugins/servlet/raven/attachment/313/stuff.txt"
      },
      {
         "id":314,
         "fileName":"stuff2.txt",
         "fileSize":"0,0 kB",
         "created":"2016-10-24T15:50:57+01:00",
         "author":"admin",
         "fileURL":"http://lenovo-pc:2990/jira/plugins/servlet/raven/attachment/314/stuff2.txt"
      }
   ],
   "comment":"new comment",
   "scenarioOutline":"Given I have entered <input_1> into the calculator\r\nAnd I have entered <input_2> into
the calculator\r\nWhen I press <button>\r\nThen the result should be <output> on the screen\r\n\r\n  Examples:
\r\n    | input_1 | input_2 | button | output |\r\n    | 20      | 30      | add    | 50     |\r\n    |
2       | 5       | add    | 7      |\r\n    | 0       | 40      | add    | 40     |",
   "examples":[
      {
         "id":1377,
         "rank":0,
         "values":[
            "input_1",
            "input_2",
            "button",
            "output"
         ],
         "status":"PASS",
         "statusDescription":"The test run has passed"
      },
      {
         "id":1378,
         "rank":1,
         "values":[
            "20",
            "30",
            "add",
            "50"
         ],
         "status":"PASS",
         "statusDescription":"The test run has passed"
      },
      {
         "id":1379,
         "rank":2,
         "values":[
            "2",
            "5",
            "add",
            "7"
         ],
         "status":"PASS",
         "statusDescription":"The test run has passed"
      },
      {
         "id":1380,
         "rank":3,
         "values":[
            "0",
            "40",
            "add",
            "40"
         ],
         "status":"PASS",
         "statusDescription":"The test run has passed"
      }
   ],
   "environments" : [
          "IOS",
          "Android"
```

```
        ]
}
```

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred getting the test run.

Update the test run. The fields that can be updated on the test run are: **status, comment, defects, evidences, examples** and **steps**.

Request

PATH PARAMETERS

parameter	type	description
id	*integer*	- ID of the test run.

Example

Example Input 1

```
{
        "status": "FAIL",
        "comment": "new comment",
        "defects": {
                "add": [
                        "test-114",
                        "test-115",
                        "test-116"
                ]
        },
        "evidences": {
                "add": [{
                        "filename": "test1.txt",
                        "contentType": "plain/text",
                        "data": "(base64 encoding...)"
                }, {
                        "filename": "test2.txt",
                        "contentType": "plain/text",
                        "data": "(base64 encoding...)"
                }],
                "remove": ["254", "443"]
        },
        "examples": [{
                "id": "1379",
                "status": "TODO"
        }]
}
```

Example Input 2

```
{
        "status": "FAIL",
        "comment": "new comment",
        "defects": {
                "add": [
                        "test-114",
                        "test-115",
                        "test-116"
                ]
        },
        "evidences": {
                "add": [{
                        "filename": "test1.txt",
                        "contentType": "plain/text",
                        "data": "(base64 encoding...)"
                }, {
                        "filename": "test2.txt",
                        "contentType": "plain/text",
                        "data": "(base64 encoding...)"
                }],
                "remove": ["254", "443"]
        },
        "steps": [{
                "id": "731",
                "status": "TODO",
                "comment": "the comment 1"
        }, {
                "id": "730",
                "status": "PASS",
                "defects": {
                        "add": [
                                "test-114",
                                "test-115",
                                "test-116",
                                "appId=a364a9c7-9ac0-3183-9175-353c1331692a&issue=SDP-5"
                        ]
                },
                "evidences": {
                        "add": [{
                                "filename": "test1.txt",
                                "contentType": "plain/text",
                                "data": "(base64 encoding...)"
                        }, {
                                "filename": "test2.txt",
                                "contentType": "plain/text",
                                "data": "(base64 encoding...)"
                        }],
                        "remove": ["274", "543"]
                }
        }]
}
```

Example Input 3

```
{
    "status": "FAIL",
    "defects": {"add":["appId=a364a9c7-9ac0-3183-9175-353c1331692a&issue=SDP-5"], "remove":["DCW-9",
"appId=a364a9c7-9ac0-3183-9175-353c1331692a&issue=SDP-1"]},
    "evidences": [],
    "steps": [
        {
            "id": 43,
            "status": "PASS",
            "comment": "",
            "defects": {"add":[], "remove":["DCW-9"]},
            "evidences": []
        },
        {
            "id": 44,
            "status": "FAIL",
            "defects": {},
            "evidences": []
        },
        {
            "id": 45,
            "status": "FAIL",
            "defects": {},
            "evidences": []
        }
    ]
}
```

Example Request

curl -H "Content-Type: application/json" -X PUT -u admin:admin --data @example.json http://yourserver / rest/raven/1.0/api/testrun/1

Responses

200 OK : **text/plain** : Successful.

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred updating the test run.

Status

- To view the status of a Test Run, you need to specify the ID of the Test Run.
- To update the status, an additional parameter is required: the Status that you want the Test Run to have.

Return a json that contains the test run status.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- ID of the test run.

Example Request

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testrun/3/status

Responses

200 OK : **text/plain** : Successful. Returns the name of the test run Status.

Example Output
PASS

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when getting the test run status.

Updates the test run status.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- ID of the test run.

QUERY PARAMETERS

parameter	type	description
status	*String*	- The status you want the test run to have.

Example Request

curl -H "Content-Type: application/json" -X PUT -u admin:admin http://yourserver/rest/raven/1.0/api/testrun/3/status?status=PASS

Responses

200 OK : **text/plain** : Successful.

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when updating the test run status.

Execution Defects

- To view the defects of a Test Run, you need to specify the ID of the Test Run.
- To add a new defect to the Test Run, a JSON with an of issue keys is required.
- To delete one or more defects from the Test Run, you need to specify the key of the issue you want to delete.

Return a json that contains an array with all the defects the test run has.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- id of the test run.

Example Request

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testrun/3/defect

Responses

200 OK : **text/plain** : Successful. Returns a json with the test run defects.

Example Output

```
[
   {
      "id":15017,
      "key":"TEST-114",
      "summary":"summary 1",
      "status":"Open"
   },
   {
      "id":15018,
      "key":"TEST-115",
      "summary":"summary 2",
      "status":"Open"
   },
   {
      "id":15019,
      "key":"TEST-116",
      "summary":"summary 3",
      "status":"Open"
   }
]
```

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when getting the test run defects.

Add new defects to the Test Run.

Request

PATH PARAMETERS

parameter	type	description
id	*integer*	- id of the test run.

Example

Example Input

```
[
   "TEST-114",
   "TEST-115",
   "TEST-116",
   "TEST-117",
   "appId=a364a9c7-9ac0-3183-9175-353c1331692a&issue=SDP-1" (in case of defects from remote JIRA servers)
]
```

Example Request

curl -H "Content-Type: application/json" -X POST -u admin:admin --data @example.json http://yourserver / rest/raven/1.0/api/testrun/2/defect

Responses

200 OK : **text/plain** : Successful.

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when inserting the defects.

Remove one or more defects from the test run.

Request

PATH PARAMETERS

parameter	type	description
id	*integer*	- ID of the test run.
issueIdOrKey	String or Integer	- ID or key of the issue you want to remove from the defects.

Example Request

curl -H "Content-Type: application/json" -X DELETE -u admin:admin http://yourserver / rest/raven/1.0/api/testrun/2/defect/TEST-421

Responses

200 OK : **text/plain** : Successful.

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when inserting the defects.

Execution Evidence

- To view the execution evidence of a Test Run, you need to specify the ID of the Test Run.
- To add new execution evidence to the Test Run, a JSON is required.
- To delete one or more execution evidence from the Test Run, you need to send a JSON with the file name of the evidence you want to delete. Another way to delete an execution evidence is to specify the evidence ID.

Return a json that contains an array with all the execution evidence the test run has.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- id of the test run.

Example Request

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testrun/3/attachment

Responses

200 OK : **text/plain** : Successful. Returns a json with the test run execution evidences.

Example Output

```
[
   {
      "id":253,
      "fileName":"TestdataPoorPerfomance.csv",
      "fileSize":"35 kB",
      "created":"2016-10-24T15:50:57+01:00",
      "author":"admin",
          "fileURL": "http://YOURJIRA/jira/plugins/servlet/raven/attachment/253/TestdataPoorPerfomance.csv"
   },
   {
      "id":254,
      "fileName":"testfile.txt",
      "fileSize":"35 kB",
      "created":"2016-10-24T16:50:57+01:00",
      "author":"admin"
          "fileURL": "http://YOURJIRA/jira/plugins/servlet/raven/attachment/254/testfile.txt"
   }
]
```

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when getting the evidences.

Add a new evidence to the test run.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- id of the test run.

Example

Example Input

```
{
   "data":"iVBORw0KGgoAAAANSUhEUgAABkIAAAO9CAYAAADezXv6AAAAAXNSR0IArs4c6QAA(...base64 file enconding)",
   "filename":"image21.jpg",
   "contentType":"image/jpeg"
}
```

Example Request

curl -H "Content-Type: application/json" -X POST -u admin:admin --data @example.json http://yourserver / rest/raven/1.0/api/testrun/2 /attachment

Responses

200 OK : **text/plain** : Successful.

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when inserting the evidences.

Remove all evidences with the same filename from the test run.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- ID of the test run.

Example

Example Input
`image.png`

Example Request

curl -H "Content-Type: application/json" -X DELETE -u admin:admin --data @example.json http://yourserver / rest/raven/1.0/api/testrun/2 /attachment

Responses

200 OK : **text/plain** : Successful.

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when deleting the evidences .

Remove the evidence with the given attachment id.

Request

PATH PARAMETERS

parameter	type	description
`id`	*Integer*	- id of the test run.
attachmentid	*Integer*	- id of the attachment we want to delete.

Example Request

curl -H "Content-Type: application/json" -X DELETE -u admin:admin http://yourserver / rest/raven/1.0/api/testrun/2/attachment/1

Responses

200 OK : **text/plain** : Successful.

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when deleting the evidences.

Comment

- To view the comment of a Test Run, you need to specify the ID of the Test Run.

- To update the comment, you need to send a JSON with the comment that you want the Test Run to have.

Return a json that contains the test run comment in raw and rendered state.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- id of the test run.

Example Request

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testrun/3/comment

Responses

200 OK : **text/plain** : Successful. Returns a json with the test run comment.

Example Output

```
{
   "raw":"this is the test run comment.",
   "rendered":"<p>this is the test run comment.</p>"
}
```

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when getting the test run comment.

Update the comment and the return a json that contains the updated test run comment in raw and rendered state.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- id of the test run.

Example

Example input

```
This is the new test run comment.
```

Example Request

curl -H "Content-Type: application/json" -X PUT -u admin:admin --data @example.json http://yourserver / rest/raven/1.0/api/testrun/2 /comment

Responses

200 OK : **text/plain** : Successful. Returns a json with the test run comment.

Example Output

```
{
   "raw":"this is the new test run comment.",
   "rendered":"<p>this is the new test run comment.</p>"
}
```

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when updating the test run comment.

Examples

- To view all examples of a Test Run, you need to specify the ID of the Test Run.
- To view or edit a specific test example, check out Test Examples - REST

Return a json that contains all of the test run examples .

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- id of the test run.

Example Request

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testrun/3/example

Responses

200 OK : **text/plain** : Successful. Returns a json with the test run examples.

Example Output


```
[
  {
    "id": 5068,
    "rank": 1,
    "values": [
      "0",
      "factorial",
      "1"
    ],
    "status": "PASS",
    "duration": "0 millisec",
    "backgrounds": [
      {
        "id": 1337,
        "rank": 1,
        "type": "background",
        "keyword": "Given ",
        "name": "a calculator I just turned on",
        "duration": "0 millisec",
        "status": "PASS"
      }
    ],
    "hooks": [
      {
        "id": 1338,
        "rank": 2,
        "type": "hook",
        "keyword": "Before",
        "name": "FactorialCalculator.setUp()",
        "duration": "0 millisec",
        "status": "PASS"
      },
      {
        "id": 1339,
        "rank": 3,
        "type": "hook",
        "keyword": "After",
        "name": "FactorialCalculator.tearDown()",
        "duration": "0 millisec",
        "status": "PASS"
      }
    ],
    "steps": [
      {
        "id": 1340,
        "rank": 4,
        "type": "scenario",
        "keyword": "Given ",
        "name": "I have entered 3 into the calculator",
        "duration": "0 millisec",
        "status": "PASS"
      },
      {
        "id": 1341,
        "rank": 5,
        "type": "scenario",
        "keyword": "When ",
        "name": "I press factorial",
        "duration": "0 millisec",
        "status": "PASS"
      },
      {
```

```
      "id": 1342,
      "rank": 6,
      "type": "scenario",
      "keyword": "Then ",
      "name": "the result should be 6 on the screen",
      "duration": "0 millisec",
      "status": "PASS"
    }
  ]
},
{
  "id": 5069,
  "rank": 2,
  "values": [
    "1",
    "factorial",
    "1"
  ],
  "status": "FAIL",
  "duration": "2 millisec",
  "backgrounds": [
    {
      "id": 1343,
      "rank": 7,
      "type": "background",
      "keyword": "Given ",
      "name": "a calculator I just turned on",
      "duration": "0 millisec",
      "status": "PASS"
    }
  ],
  "hooks": [
    {
      "id": 1344,
      "rank": 8,
      "type": "hook",
      "keyword": "Before",
      "name": "FactorialCalculator.setUp()",
      "duration": "0 millisec",
      "status": "PASS"
    },
    {
      "id": 1345,
      "rank": 9,
      "type": "hook",
      "keyword": "After",
      "name": "FactorialCalculator.tearDown()",
      "duration": "0 millisec",
      "status": "PASS"
    }
  ],
  "steps": [
    {
      "id": 1346,
      "rank": 10,
      "type": "scenario",
      "keyword": "Given ",
      "name": "I have entered 4 into the calculator",
      "duration": "0 millisec",
      "status": "PASS"
    },
    {
      "id": 1347,
      "rank": 11,
      "type": "scenario",
      "keyword": "When ",
      "name": "I press factorial",
      "duration": "0 millisec",
      "status": "PASS"
    },
    {
```

```
        "id": 1348,
        "rank": 12,
        "type": "scenario",
        "keyword": "Then ",
        "name": "the result should be 65 on the screen",
        "duration": "2 millisec",
        "logError": "java.lang.AssertionError: \nExpected: is <65L>\n     but: was <24L>\r\n\tat org.hamcrest.
MatcherAssert.assertThat(MatcherAssert.java:20)\r\n\tat org.junit.Assert.assertThat(Assert.java:956)\r\n\tat
org.junit.Assert.assertThat(Assert.java:923)\r\n\tat com.xpandit.automation.cucumber.FactorialCalculator.
theResultShouldBeOutputOnTheScreen(FactorialCalculator.java:47)\r\n\tat .Then the result should be 65 on the
screen(com/xpandit/automation/cucumber/2_factorial_error.feature:11)",
        "status": "FAIL"
      }
    ]
  }
]
```


400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when getting the test run examples.

Test Steps

- To view all the test steps of a Test Run, you need to specify the ID of the Test Run.
- To view or edit a specific test step, check out Test Steps - REST

Return a json that contains all of the test run steps.

Request

PATH PARAMETERS

parameter	type	description
`id`	*integer*	- id of the test run.

Example Request

curl -H "Content-Type: application/json" -X GET -u admin:admin http://yourserver/rest/raven/1.0/api/testrun/3/step

Responses

200 OK : **text/plain** : Successful. Returns a json with the test run steps.

Example Output

```
[
   {
      "id":729,
      "index":1,
      "step":{
         "raw":"ssaf",
         "rendered":"<p>ssaf</p>"
      },
      "data":{
         "raw":"asdf",
         "rendered":"<p>asdf</p>"
      },
      "result":{
         "raw":"asdfasdf",
         "rendered":"<p>asdfasdf</p>"
      },
      "attachments":[
      ],
      "status":"EXECUTING",
      "comment":{
         "raw":"asdasdasdasdasd",
         "rendered":"<p>asdasdasdasdasd</p>"
      },
      "defects":[
         {
            "id":15018,
            "key":"CALC-115",
            "summary":"Ad-hoc execution for CALC-93",
            "status":"Open"
         }
      ],
      "evidences":[
         {
            "id":216,
            "fileName":"1 (24).feature",
            "fileSize":"0,4 kB",
            "created":"2016-10-24T15:50:57+01:00",
            "author":"admin"
                        "fileURL": "http://YOURJIRA/jira/plugins/servlet/raven/attachment/253/1 (24).feature"
         }
      ]
   },
   {
      "id":730,
      "index":2,
      "step":{
         "raw":"asfd",
         "rendered":"<p>asfd</p>"
      },
      "data":{
         "raw":"aaa",
         "rendered":"<p>aaa</p>"
      },
      "result":{
         "raw":"aaaa",
         "rendered":"<p>aaaa</p>"
      },
      "attachments":[
      ],
      "status":"FAIL",
      "comment":{
         "raw":"aaaaa\n",
         "rendered":"<p>aaaaa</p>"
      },
      "defects":[
      ],
      "evidences":[
      ]
   }
]
```

400 BAD_REQUEST : **text/plain** : Returns the error.

401 UNAUTHORIZED : **text/plain** : The Xray license is not valid.

500 INTERNAL SERVER ERROR : **text/plain** : An internal error occurred when getting the test run steps.