Project Settings: Test Step Fields

As a project administrator, you can define new Test Step Fields to use in the context of your project.

All projects start with 3 Test Step Fields, **Action**, **Data** and **Expected Result**. These are the default Test Step fields and cannot be deleted, but can be set to optional/required or/and disabled with the exception of the **Action** which is always a required field.

Each project can have a maximum of 6 **Test Step Fields** (including the default ones) and the fields can be of the following types:

- Toggle Switch
- Date Picker
- Date Time Picker
- Number
- Radio Buttons
- Select List
- Select List (Multiple)
- Text
- Text (Single Line)
- User Picker

Test Step Fields

Create Test Step Field

Name	Description	Type	Flags	Actions
Action (action)	The action to be reproduced by the tester.	Text	NATIVE REQUIRED	
Data (data)	Any data the related step requests (e.g., login credentials) to be used by the tester.	Text	NATIVE	•••
Expected Result (result)	The behavior that the step should accomplish.	Text	NATIVE	•••

- Create a Test Step Field
- Delete a Test Step Field
- Edit a Test Step Field
- Rerank a Test Step Field

Create a Test Step Field

To create a new **Test Step Field**, press the **Create Test Step Field** button, fill out the following fields, and press **Create**:

- **Type**: the type of the Test Step Field;
- **Name**: the name of the Test Step Field, which is always is **required**;
- **Description**: the description of the Test Step Field;
- **Required**: whether the Test Step Field is required when adding/creating a new Test Step to the Test issue;

Delete a Test Step Field

To delete a **Test Step Field**, press the "**...**" icon and then **Delete** option.


Note: When a **Test Step Field** is deleted all its information will be removed from the Test Steps.

Edit a Test Step Field

To edit a **Test Step Field**, press the "**...**" icon and then **Edit** option. You can change the **Name**, **Description** and whether the field is **Required** or not.

Test Step Fields

Create Test Step Field

Name	Description	Type	Flags	Actions
Execution Domain		Select List (Multiple), 6 option(s)		···
Action (action)	The action to be reproduced by the tester.	Text	NATIVE REQUIRED	
Data (data)	Any data the related step requests (e.g., login credentials) to be used by the tester.	Text	NATIVE	
Expected Result (result)	The behavior that the step should accomplish.	Text	NATIVE	

✎ Edit
— Set as Required
✓ Disable
🗑 Delete

Edit Test Step Field

Type

Select List (Multiple) ⌄

Values *

Browser ✕   Command Line ✕   Postman ✕   RDBMS ✕   Email ✕   Backoffice ✕   ⊗ ⌄

Insert new values by typing and reorder by dragging.

Name *

Execution Domain

Description

Required

☐ This test step field is required

Save   Cancel

Also, to change the order of the value options of a Select Field simply drag the options to the desired position.

Edit Test Step Field

Type

Select List (Multiple) ⌄

Values *

Browse... ✕   Backoffice ✕   ...nd Line ✕   Postman ✕   RDBMS ✕   Email ✕

Backoffice ✕   [ ]   ⊗   ⌄

Insert new values by typing and reorder by dragging.

Name *

Execution Domain

Description

[ ]

Required

☐ This test step field is required

Save   Cancel

It is also possible to **Disable** the **Test Step Field**, which will hide the field in the Test Issue, even if it already has a value, and to set it **Optional** or **Required** using the "**...**" icon.

Test Step Fields

Create Test Step Field

Name	Description	Type	Flags	Actions
Execution Domain		Select List (Multiple), 6 option(s)		**...**
Action (action)	The action to be reproduced by the tester.	Text	NATIVE REQUIRED	✏ Edit
Data (data)	Any data the related step requests (e.g., login credentials) to be used by the tester.	Text	NATIVE	— Set as Required
Expected Result (result)	The behavior that the step should accomplish.	Text	NATIVE	✓ Disable
				🗑 Delete

Test Step Fields

Create Test Step Field

Name	Description	Type	Flags	Actions
Execution Domain		Select List (Multiple), 6 option(s)	REQUIRED	**...**
Action (action)	The action to be reproduced by the tester.	Text	NATIVE REQUIRED	✏ Edit
Data (data)	Any data the related step requests (e.g., login credentials) to be used by the tester.	Text	NATIVE	✓ Set as Optional
Expected Result (result)	The behavior that the step should accomplish.	Text	NATIVE	✓ Disable
				🗑 Delete

Rerank a Test Step Field

It's possible to change the order of the **Test Step fields** by dragging the rows. The order of the test step fields in the configuration screen is the same that will be shown in the tests issue screen.

Test Step Fields

Create Test Step Field

	Name	Description	Type	Flags	Actions
⠿	Execution Domain		Select List (Multiple), 6 option(s)	REQUIRED	•••
⠿	Action (action)	The action to be reproduced by the tester.	Text	NATIVE REQUIRED	
⠿	Data (data)	Any data the related step requests (e.g., login credentials) to be used by the tester.	Text	NATIVE	•••
⠿	Expected Result (result)	The behavior that the step should accomplish.	Text	NATIVE	•••